



Emergency Equipment

Serving Maryland and Delaware Fire/EMS Personnel since 1990

NEW DELIVERY

Wilmington Manor Fire Company - New Castle County, DE
2009 Spartan Gladiator / Rosenbauer Rescue Pumper



Vehicle Description:

Chassis - Spartan Gladiator LFD w/10" raised roof

Wheelbase - 216"

Travel Height - 128" (10'-8")

Travel Length - 430" (35'-10")

Seating Capacity - 6-person, (5) SCBA seats

Front Axle / Susp. - Meritor MFS-20 / Taperleaf w/shocks rated @ 21,500 lbs.

Rear Axle / Susp. - Meritor RS-25-160 / Reyco spring rated @ 27,000 lbs.

Engine - Cummins ISM 450 HP @ 1,550 lb./ft.

Transmission - Allison 4000 EVS, 6-speed automatic

Fire Pump - Hale QMAX 1500 GPM single-stage

Booster Tank - 500 gallons

Gauges - Class 1

Intakes - (1) 6" on each pump panel - both with Hale MIV, (1) 2-1/2" on L/S

Discharges - 2-1/2" in front bumper; (2) 2-1/2" on L/S pump panel; (1) 2-1/2" and (1) 4" on R/S pump panel; 3" deck gun; (1) 2-1/2" on rear of body

Hoseload - (2) crosslays w/300' of 1-3/4" each, 150' of 1-3/4" in front bumper, Hosebed: 300' of 2-1/2", 500' of 3", and 1,500' of 5"

Body Material - Extruded aluminum w/aluminum subframe

Compartment Configuration - L/S and R/S compartments are full-height/full-depth, side mount pump controls, (4) upper coffin compartments

Warning Lights - Whelen FN72VLED 72" LED lightbar w/Opticom, Whelen LED cab/body warning lights, Whelen TA870L LED Traffic Advisor

Audible Warning - (2) 24" Grover Stuttertone air horns, PowerCall DX-5100 electronic siren, Federal Q2B electro-mechanical siren, Federal Signal BP200-EF siren speaker

Ladders - 24' 2-section, 12' roof, 10' folding

Additional - Akron 3440 DeckMaster electronically controlled deck gun w/12" extend-a-gun, Firecom 3010 vehicle intercom system, Harrison 20kW hydraulic generator, (3) Voyager backup cameras w/flat screen monitor, (2) Hannay ECR1600 Series electrical reels, (3) Hurst hydraulic reels including one in the front bumper, (2) Hannay 1500 Series low-pressure air reels supplied by (2) 6,000 PSI DOT bottles, (2) FRC Optimum 750W-120V brow lights, (2) FRC Focus 1,000W-240V tripod lights on rear, (4) FRC Optimum 750W-120V telescoping recessed lights mounted in upper body sides, Will-Burt NightScan NS15-6000O-DT light tower with (4) FRC Optimum 1500W-240V lights, Warn 9,000 pound portable winch with receivers on (4) sides, multiple shelves, trays, and toolboard, custom tool mounting by DPC.

